



Pictures show sample configurations, real product may vary.



COMPUTER UNIT

Processor	AMD EPYC™ 9005 series
Onboard graphics	Aspeed AST2600 256MB
Chipset	SoC
Memory	24 x DDR5 RDIMM
Drives	OS: 2 x M.2 NVMe SSD; Data: up to 10 x 2.5" hot-swap U.2 SSD (7.68, 15.36, 30.72 TB); Meta: 2 x 2.5" hot-swap U.2 SSD (3.84, 7.68, 15.36 TB)
TPM	TPM 2.0
Remote-Management	ASMB11-iKVM (on-board)
Front I/O	Power On/Off; LED indicator
Rear I/O	2 x USB Type-A (3.2 Gen1) 1 x VGA 1 x IPMI 2 x GbE LAN 2 x 25/10GbE LAN
Cooling	8 x 40x56 mm PWM hot-swap fans; passive CPU heat sink
NIC	BROADCOM® NetXtreme P225P 2x25/10GbE SFP28

POWER

Power input	100-240 V AC; 50-60 Hz
Power supply	1+1 redundant PSU 1600W; Titanium

SYSTEM

Dimensions (WxDxH)	33.17 x 17.68 x 1.73"
Material	Steel
Weight	Up to 30 kg (depending on configuration)
Mounting	via slide rails in 19" rack

ENVIRONMENTAL CONDITIONS

	Storage	Operating
Temperature	-40°C ~ 70°C	10°C ~ 35°C
Humidity ¹ (rel.)	20% ~ 90%	

CERTIFICATIONS

CE

*optional

²depending on configuration

¹non-condensing

³pending