



Pictures show sample configurations, real product may vary.



COMPUTER UNIT

Processor	DUAL AMD EPYC™ 9005 series
Onboard graphics	ASPEED AST2600
Chipset	SoC
Memory	24 x DDR5 RDIMM
Drives	OS: 2 x M.2 NVMe SSD; Data: up to 20 x 2.5" hot-swap U.2 SSD (7.68, 15.36, 30.72 TB); Meta: up to 4 x 2.5" hot-swap U.2 SSD (3.84, 7.68, 15.36 TB)
TPM	TPM 2.0
Remote-Management	ASPEED AST2600 BMC
Front I/O	Power On/Off, VGA 2 x USB LED
Rear I/O	2 x USB Type-A (3.2 Gen1) 1 x miniDP 1 x IPMI 2 x 25/10GbE LAN
Cooling	6 x 60x56 mm PWM hot-swap fans; passive CPU heat sink
NIC	BROADCOM® NetXtreme P225P 2x25/10GbE SFP28

POWER

Power input	100-240 V AC; 50-60 Hz
Power supply	1+1 redundant PSU 2000 W; Titanium

SYSTEM

Dimensions (WxDxH)	30.31 x 17.24 x 3.43"
Material	Steel
Weight	Up to 30 kg (depending on configuration)
Mounting	via slide rails in 19" rack

ENVIRONMENTAL CONDITIONS

	Storage	Operating
Temperature	-40°C ~ 70°C	5°C to 35°C
Humidity ¹ (rel.)	20% ~ 90%	

CERTIFICATIONS

CE

*optional

²depending on configuration

¹non-condensing

³pending