



Pictures show sample configurations, real product may vary.

## COMPUTER UNIT

<b>Processor</b>	2 x AMD EPYC™ 9115 (16C)
<b>Onboard graphics</b>	Aspeed AST2600
<b>Memory</b>	1.024 GB DDR5 6400 ECC REG
<b>Drives</b>	OS: 2 x 3.840 GB 2.5" NVMe SSD; DATA: up to 6 x 7.680 GB NVMe SSD*
<b>LAN</b>	2 x 10 GbE (Intel® X550-AT2)
<b>Remote-Management</b>	IPMI2.0 with iKVM (ASPEED AST2600) dedicated IPMI LAN port
<b>Expansion slots</b>	4 x PCIe 5.0 x16 FH/FL via Riser 2 x PCIe 5.0 x16 HH/HL via Riser
<b>Front I/O</b>	1 x Power w/ LED 1 x Reset 1 x UID w/ LED 2 x LAN LED 1 x Warning LED 2 x USB 3.2 Gen1 ports (Type A)
<b>Rear I/O</b>	2 x USB-A (3.2 Gen1) 1 x VGA 2 x RJ45 (10 GbE), 1 x dedicated IPMI (1GbE) 2 x IEC connector (C14)
<b>Cooling</b>	Active
<b>Graphic card(s)</b>	1 x NVIDIA L4 24 GB GPU*
<b>NIC</b>	Intel® Ethernet-Netzwerkadapter E810-XXVDA2 (2 x 25GbE SFP28) PCIe 4.0 x8 LP*

## POWER

<b>Power input</b>	100-240 V AC; 50-60 Hz
<b>Power supply</b>	1U Redundant CRPS 1+1 2700 W 80+ Titanium
<b>Power consumption</b>	Max 15.5 A

## SYSTEM

<b>Dimensions (WxDxH)</b>	33.46" x 17.63" x 3.43" (850 x 448 x 87mm)
<b>Material</b>	Steel
<b>Weight</b>	Approx. 31 kg
<b>Mounting</b>	Rackmount w rails
<b>Coating/Color</b>	w/o

## ENVIRONMENTAL CONDITIONS

	Storage	Operating
<b>Temperature</b>	-40°F ~ 158°F (-40°C ~ 70°C)	50° F~ 95° F (10° C ~ 35° C)
<b>Humidity<sup>1</sup> (rel.)</b>	90% at 35° C	90% at 35° C

## PACKAGING

	Weight	Dimensions (WxDxH)
<b>System incl. packaging</b>	Approx. 63 kg	

\*optional

<sup>2</sup>depending on configuration<sup>1</sup>non-condensing<sup>3</sup>pending