



Pictures show sample configurations, real product may vary.

COMPUTER UNIT

Processor	2 x AMD EPYC™ 9535 (64C)
Onboard graphics	Aspeed AST2600
Memory	2.048 GB DDR5 6400 ECC REG
Drives	OS: 2 x 3.840 GB 2.5" NVMe SSD DATA: 6 x 15.360 GB NVMe SSD
LAN	2 x 10GbE (Intel X550-AT2)
Remote-Management	IPMI2.0 with iKVM (ASPEED AST2600) dedicated IPMI LAN port
Expansion slots	4 x PCIe 5.0 x16 FH/FL via Riser 2 x PCIe 5.0 x16 HH/HL via Riser
Front I/O	1 x Power w/ LED 1 x Reset 1 x UID w/ LED 2 x LAN LED 1 x Warning LED 2 x USB 3.2 Gen1 ports (Type A)
Rear I/O	2 x USB-A (3.2 Gen1) 1 x VGA 2 x RJ45 (10 GbE) 1 x dedicated IPMI (1 GbE) 2 x IEC connector (C14)
Cooling	Active
Graphic card(s)	Up to 4 x NVIDIA RTX 6000 48 GB GPU*
NIC	Intel® Ethernet network adapter E810-XXVDA2 (2 x 25 GbE SFP28) PCIe 4.0 x8*; Intel® Ethernet network adapter E810-CQDA2 (2 x 100 GbE QSFP28) PCIe4 x16

POWER

Power input	100-240 V AC; 50-60 Hz
Power supply	1U Redundant CRPS 1+1 2700 W 80+ Titanium
Power consumption	Max 15.5 A

*optional

²depending on configuration¹non-condensing³pending

SYSTEM

Dimensions (WxDxH)	33.46" x 17.63" x 3.43" (850 x 448 x 87mm)
Material	Steel
Weight	Approx. 31 kg
Mounting	Rackmount w rails
Coating/Color	w/o

ENVIRONMENTAL CONDITIONS

	Storage	Operating
Temperature	-40°F ~ 158°F (-40°C ~ 70°C)	50° F~ 95° F (10° C ~ 35° C)
Humidity¹ (rel.)	90% at 35° C	90% at 35° C

PACKAGING

	Weight	Dimensions (WxDxH)
System incl. packaging	Approx. 63 kg	