

POLYTOUCH® DIGITAL SIGNAGE 55

4010078939



Pictures show sample configurations, real product may vary.

DISPLAY

Surface treatment	Anti-Glare (25% Haze)
Display size*	55"
Aspect ratio	16:9
Resolution	3840 x 2160 (4K)
Colours	16.7 million
Brightness	700 cd/m ²
Contrast ratio	≥ 1200:1
Visual angle	178°(H) / 178°(V)
Interfaces	2 x HDMI-in (HDMI 2.0) 2 x DP-in (DP 1.2) 1 x DP-out (Daisy chain, up to 4K input) 1 x Audio Out (3.5 mm stereo jack) 1 x RS232-in (RJ45, common used for IR in) 1 x RS232-out (RJ45, support IR out) 2 x Speaker 10 W (6 Ω) 1 x USB (2.0, Firmware update only)

*others on request

POWER

Power supply	100-240 V AC, 50/60 Hz
Power consumption	165 W

SYSTEM

Dimensions (WxDxH)	1225 x 689 x 61.7 mm
Material	Aluminum
Weight	11.9 kg
Mounting	VESA 400 x 400, mounting holes diameter 6 mm
Colour	Black
Accessories	Remote controller, power cord

ENVIRONMENTAL CONDITIONS

	Storage	Operating
Temperature	-20°C to +60°C	0°C to 50°C
Relative humidity	5% to 95% ¹	10% to 85% ¹

¹ non-condensing

CERTIFICATIONS

CE

PACKAGING & INDIVIDUAL WEIGHTS

	Weight net	Dimensions (WxHxD)	Stack
System	21 kg	1379 x 853 x 209 mm	carton

INTENDED USE/APPLICATION

The device is only to be used as a digital signage screen for displaying visual content, images, slideshows indoors in combination with the intended fastening elements. Other fasteners require the prior written consent of the manufacturer.

DIMENSIONS

Pictures show sample configurations, real product may vary.

