

AKHET® Endurance F4U350i



Pictures show sample configurations, real product may vary.



COMPUTER UNIT

| | |
|-------------------|---|
| Processor | Intel® Core™ processors (12 th /13 th /14 th Gen) |
| Graphics | Intel® UHD Graphics 7xx |
| Chipset | Intel® R680E |
| Memory | up to 128 GB DDR5 |
| Drives | up to 4 TB M.2 NVMe SSD BootDrive up to 4 TB NVMe Datadrive |
| LAN | 1 x 1 GbE (Intel® i219LM) 2 x 2.5 GbE (Intel® i226LM) |
| Remote Management | Intel® iAMT |
| Expansion slots | 1 x PCIe x16 3 x PCIe x4 2 x PCIe x1 1 x PCI 32Bit |
| Front I/O | 4 x DisplayPort V1.4a up to 8K 3 x RJ45 4 x USB 3.2 Gen1 (Type-A) 1 x USB 3.2 Gen 2 (Type-C) 4 x USB 3.2 Gen2 (Type-A) 1 x RS232 Audio, AC-in, Power button Hot-swap trays |
| Rear I/O | Dust filter (exchangeable) |
| Cooling | Active |

POWER

| | |
|-------------------|--------------|
| Power supply | 100-240 V AC |
| Power consumption | TBD |

SYSTEM

| | |
|--------------------|--------------------------------|
| Dimensions (WxDxH) | 430 x 346 x 178 mm |
| Material | Steel, RAL 9005 powder coated |
| Weight | Approx. 15 kg |
| Mounting | 4HE Rack (w/o rails), Wallmont |

ENVIRONMENTAL CONDITIONS

| | Storage | Operating |
|-------------|-------------------------|-------------------------|
| Temperature | -20°C to +60°C | 0°C to 35°C |
| Humidity | 10% to 95% ¹ | 10% to 80% ¹ |

¹ non-condensing

CERTIFICATIONS

CE

INTENDED USE

AKHET® Rack Systems are specifically designed to be mounted in standard equipment rack. The intended use includes data centres, virtualization, database management with specific needs of various workloads and applications. Operation and service of the product should be carried out by instructed personnel only to avoid risk of injury from electrical shock or energy hazard.

DIMENSIONS

Pictures show sample configurations, real product may vary.

