
4010081365







DISPLAY

Front	1.2 mm strengthened glass		
Coating	Anti-Glare		
Surface hardness	7H		
Display size	21.5"		
Aspect ratio	16:9		
Display type	Active matrix TFT LCD with LED backlighting, A+ Grade		
Resolution	1920 x 1080 (Full HD)		
Colors	16.7 million		
Brightness	250 cd/m ²		
Viewing angle	Horizontal (left/right): 170° /vertical (up/down): 170°		
Contrast ratio	1000:1		
Backlight lamp life	typ. 30,000 hours to half brightness		
Touch technology	PCAP, OGS		

Touch driver support Windows® 10 – Windows® 11

COMPUTER UNIT

Processor	Intel 10 th Gen i3-10100TE Comet Lake 4C/8T 2.3 GHz		
Chipset	Q470		
Graphics	Intel® UHD graphics 630		
Memory	8 GB DDR4		
Storage	128 GB SSD		
LAN	2 x 1GbE LAN		
OS	Windows® 10 (optional)		

POWER

Power input C13, 100 – 240 V AC, 50/60 Hz

SYSTEM

Material	Steel, powder coated		
Dimensions (WxDxH)	405.9 x 328.9 x 550.3 mm		
Weight	19 kg		
Mounting	Desk mount, wallmount, pedestal		
Colour	RAL 7016; RAL 9010		

CONFIGURATION

Scanner/Imager	Datalogic Magellan 1500i		
Payment	Prepared for Ingenico Desk 5000		
Printer	Epson TM-T88VII		
Handheld scanner	Datalogic Gryphon GD4520		

Pole light with SEDU controller

ENVIRONMENTAL CONDITIONS

	Storage	Operating	
Temperature	-20°C to +60°C	15°C to 35°C	
Humidity 5% to 95% ¹		20% to 90% ¹	

¹ non-condensing

CERTIFICATIONS

CE

PACKAGING & INDIVIDUAL WEIGHTS

	Weight net	Dimensions	Stack
	gross		
Complete system	19 kg	685 x 385 x 485 mm	max. 3 systemes
	25 kg		on top of each other

INTENDED USE/APPLICATION

The device is only to be used as a touch panel in combination with the intended fastening elements (pedestal, wall or table bracket). Other mounting elements must be specified accordingly for the device. The central component of the system consists of a computer with a touch screen. The touchscreen uses Projective Capacitive Technology (PCT) to recognize touch. The system is supplemented by built-in peripheral components. The device can be connected to an IT power distribution system.



DIMENSIONS

Pictures show sample configurations, real product may vary.

