

POLYTOUCH® POS 400A

4010079764



Pictures show sample configurations, real product may vary.



DISPLAY

Surface treatment	Glare
Display size	15.6" (main display, touch) 10.1" (customer display, non-touch)
Angle of inclination	Freely adjustable
Aspect ratio	16:9
Front glass	G+G, 7H
Touch technology	10 points capacitive touch screen
Resolution	1920 x 1080 (main display), 800 x 1280 (second display)
Colours	262 k (6bit), 45 % NTSC
Brightness	Typ. 250 cd/m ²
Contrast ratio	Typ. 500:1
Visual angle	Typ. 45°/45°/20°/40° (CR>10)

COMPUTER UNIT

Processor	Quad-core, Cortex-A55, up to 2.0 GHz
Chipset	RK3568
Graphics	ARM Mali-G52-2EE
Memory	4 GB DDR4
Storage	32 G eMMC
LAN	10 M/100 M
BT	5.0
WiFi	2.4 G/5 G dual-band Wi-Fi
OS	Android 11

POWER

Power input	24 V; 2.75 A
-------------	--------------

SYSTEM

Dimensions (WxDxH)	210 x 362 x 375 mm
Material	Anodised aluminum, plastic
Weight	3.95 kg
Colour	Space black

CONFIGURATION

Interfaces	1 x RJ45 1 x DC-in 1 x RJ12 1 x RJ11 4 x USB 2.0 1 x TF expansion card 1 x 3.5 mm Audio output
Printer	80 mm thermal printer with auto cutter

ENVIRONMENTAL CONDITIONS

	Storage	Operating
Temperature	-12°C to +40°C	0°C to 40°C
Relative humidity	10% to 90% ¹	5% to 90% ¹

¹ non-condensing

CERTIFICATIONS

CE
FCC (ready in 03/2024)

PACKAGING & INDIVIDUAL WEIGHTS

	Weight net	Dimensions (LxWxH)	Stack
System	3.95 kg	410 x 290 x 467 mm	Carton box

DIMENSIONS

Pictures show sample configurations, real product may vary.

