POLYTOUCH® PLS PUCK GEN. 4 (V8)



Pictures show sample configurations, real product may vary.

CHASSIS

Dimensions (HxWxD) 59 x 59 x 13 mm

Weight	37 gr			
Protection class	IP 22			
Tested height of fall	TRN			

ENERGY MANAGEMENT

Battery	2 x 1000 mAh, exchangeable*			
Lifetime 24 months (based on 40 pages per day)				
	Stress test: 45,000 pages until battery empty			
* Only a service technician is authorized to replace the battery. Otherwise the				

^{*} Only a service technician is authorized to replace the battery. Otherwise the warranty will be void.

COMMUNICATION

Radio	Frequency 2.4 GHz BLE; RFID: Fudan/MiFare FM-1108 1K 13.56Mhz
Operational range	Non-line of sight (NLoS): up to 100 m Line of sight (LoS): up to 200 m

PCB

Signalling	RGB LED; vibration alarm; acoustic signal
Chip	nRF52 Series flash-based SoC, Bluetooth 5, NFC, Sensitivity
	of -96 dbm for BLF

CERTIFICATIONS

C	E	2,	F	C	C	2

 $^{^2\,} pending$

NOTICE

Risk of damage to the device from aggressive cleaning agents. Only use mild disinfectants for cleaning.



POLYTOUCH®

DIMENSIONS

 $\hbox{Pictures show sample configurations, real product may vary.}$











