

# POLYTOUCH® CURVE 32 MINI



Pictures show sample configurations, real product may vary.



## DISPLAY

Screen size	32"
Surface treatment	Anti-Glare
Orientation	Landscape
Resolution	1920 x 1080 (Full HD)
Brightness	500 cd/m <sup>2</sup>
Contrast	3000 : 1
View angle	178° h/v
Touch technology	Projected Capacitive Touch (PCT)

## COMPUTER UNIT

Processor	10 <sup>th</sup> Generation Intel® Core™ i3 (i5 / i7 optional)
Graphics	Intel® UHD Graphics
Memory	8 GB DDR-4 (up to 16 GB)
Storage	256 GB mSATA SSD
LAN	2 x 1GbE LAN
Interfaces	1 x DC-out 4 x USB 2.0 4 x USB 3.0 2 x COM 2 x RJ45 1 x DisplayPort
OS*	Windows® 11

\*optional

## POWER

Power input	100–240 V
Connector	IEC cable C13 (AC Mains OVC II)
Current input	max. 7 A
Power consumption	typical 230 W

## SYSTEM

Material	Steel, powder coated
Dimensions (WxDxH)	792 x 500 x 1218 mm (system) 650 x 500 x 1077 mm (pedestal only)
Weight	79.63 kg (pedestal incl. display) 55.16 kg (pedestal only)
Mounting	Standing device

## ENVIRONMENTAL CONDITIONS

	Storage	Operating
Temperature	–20°C to +60°C	10°C to 35°C
Humidity	5% to 95% <sup>1</sup>	20% to 90% <sup>1</sup>

<sup>1</sup> non-condensing

## CERTIFICATIONS

CE

## INTENDED USE/APPLICATION

The device is only to be used as a touch panel in combination with the intended fastening elements (pedestal, wall or table bracket). Other fasteners require the prior written consent of the manufacturer. The central component of the system consists of a computer with a touch screen. The touchscreen uses Projective Capacitive Technology (PCT) to recognize touch. The system is supplemented by built-in peripheral components. The device can be connected to an IT power distribution system.

## DIMENSIONS

Pictures show sample configurations, real product may vary.

